

10W30 SEMI SYNTHETIC

API SN/CF

Product Description

AM Semi Synthetic Gasoline Engine Oil is premium quality engine oils. Formulated from high performance hydrocracked base oils combined with selected synthetic base fluids and selected additives to exceed API SN/CF standard. It provided higher performance levels, improved engine cleanliness, increased fuel economy and reduced oil consumption. It contains enhanced detergents, dispersants, anti-oxidants, and anti-wear and corrosion prevention properties. AM Semi Synthetic Gasoline Engine Oil is recommended for all modern technology gasoline engines.

Features & Benefits

- Engineered to increase fuel economy by reducing oil consumption
- Provides excellent protection against sludge and varnish deposits
- Enhanced anti-wear properties – reduced wear which can lead to lower maintenance costs
- Effective wear and deposit control- longer engine life and reliable operation
- High viscosity index and shear stability
- Enhanced high and low temperature protection in severe driving Conditions

Product Description

- API SN Plus, SN/CF

Typical Properties

| Properties | Unit | Method | 10W30 |
|-------------------|---------|------------|-------|
| APPEARANCE | - | VISUAL | B&C |
| VISCOSITY 40°C | cSt | ASTM D445 | 68.91 |
| VISCOSITY 100°C | cSt | ASTM D445 | 10.56 |
| VISCOSITY INDEX | - | ASTM D2270 | 141 |
| COLOR | - | ASTM D1500 | L3.0 |
| TOTAL BASE NUMBER | mgKOH/g | ASTM D2896 | 7.4 |
| CCS @-25°C | cPs | ASTM D5293 | 6,102 |
| FLASH POINT | °C | ASTM D92 | 224 |
| POUR POINT | °C | ASTM D6749 | -36 |

**More specified products information are available upon request*