

15W40 SEMI SYNTHETIC

API CI-4/SL

Product Description

AM Semi Synthetic Diesel Engine is premium quality engine oils. Formulated from high performance hydrocracked base oils combined with selected synthetic base fluids and selected additives to exceed API CI-4/SL standard. AM Diesel Engine Oil is recommended for diesel engine with direct injection (DI) and commonrail direct injection (CDI) systems, diesel engine equipped with turbo-charged and EGR systems. Furthermore, it is applicable for the vehicle which install LPG / NGV / CNG.

It maintains superior engine performance, protects engine parts from heavy-load conditions, resists to heat and provides long oil drain interval resulting oil and fuel economy and cost saving maintenance.

Features & Benefits

- Helps extend oil drain interval
- Reduces operating costs and oil consumption
- Excellent Wear protection, engine cleanliness and low combustion residues
- Excellent viscosity retention

Product Description

- API CI-4/SL
- ACEA E7-16
- Cat ECF-2/1A2
- Cummins CES 20076/ 20077/ 20078
- Detroit DFS 93K215
- Mack EO-M/ EO-M PLUS/ EO-N
- Volvo VDS-3
- Renault RLD-2
- MB 228.3
- MAN M 3275
- MTU Category 2
- Deutz DQC III-18
- JASO DH-1 Engine Test Demo

Typical Properties

Properties	Unit	Method	15W40
APPEARANCE	-	VISUAL	B&C
VISCOSITY 40°C	cSt	ASTM D445	115.6
VISCOSITY 100°C	cSt	ASTM D445	15.22
VISCOSITY INDEX	-	ASTM D2270	137
COLOR	-	ASTM D1500	L1.5
TOTAL BASE NUMBER	mgKOH/g	ASTM D2896	11.0
CCS @-20°C	cPs	ASTM D5293	5,641
FLASH POINT	°C	ASTM D92	238
POUR POINT	°C	ASTM D6749	-30

**More specified products information are available upon request*