

5W40 FULLY SYNTHETIC API SN/CF

Product Description

AM Synthetic Gasoline Engine Oil is a fully synthetic motor oil. Formulated from synthetic base fluids and selected additives to exceed API SN/CF standard. It provides excellent thermal and oxidation stability, excellent deposit control. It contains enhanced detergents, dispersants, anti-oxidants, and anti-wear and corrosion prevention properties. AM Synthetic Gasoline Engine Oil is recommended for all modern technology gasoline engines.

Features & Benefits

- Excellent Enhanced thermal and oxidation stability – reduced engine deposits, build up of harmful
- Excellent control sludge and deposit produced in hot zones within an engines
- Enhanced anti-wear properties – reduced wear which can lead to lower maintenance costs
- Longer engine life and reliable operation
- High viscosity index and shear stability
- Enhanced high and low temperature protection in severe driving conditions

Product Description

- API SN Plus, SN/CF

Typical Properties

Properties	Unit	Method	5W40
APPEARANCE	-	VISUAL	B&C
VISCOSITY 40°C	cSt	ASTM D445	91.55
VISCOSITY 100°C	cSt	ASTM D445	15.05
VISCOSITY INDEX	-	ASTM D2270	173
COLOR	-	ASTM D1500	L3.0
TOTAL BASE NUMBER	mgKOH/g	ASTM D2896	7.4
CCS @-30°C	cPs	ASTM D5293	5,540
FLASH POINT	°C	ASTM D92	234
POUR POINT	°C	ASTM D6749	-39

**More specified products information are available upon request*